



TUBEX STANDARD PLUS TREESHelters

Data Sheet



The premium TUBEX treeshelter, incorporating all the regular TUBEX features to provide protection and improved growth in an efficient and economical way.

For those tougher jobs, providing a slightly wider diameter than the TUBEX Standard, the TUBEX Standard Plus comes in a range of heights from 4' to 6'. Studies indicate that the accelerated growth induced by a treeshelter reduces as the diameter of the shelter increases - a range of diameters between 2" and 8" provide optimum results. The TUBEX Standard Plus comes in a nest of 5 diameters between 3.15" and 4.7". TUBEX precision engineering has allowed us to produce a nest of shelters (required for efficient transportation) with a minimum diameter range whilst allowing for easy unpacking of the nest – even with premium quality ratchet ties pre-fitted.

Hints and Tips

- Use a well-driven quality stake to a soil depth of at least 1' (maybe deeper in cultivated soil).
- If tree fills shelter diameter before the normal degradation period (5 years+), consider removing the shelter or manually initiating the laserline split.
- See TUBEX Forestry brochure for advice on choice and use of TUBEX products.

Quick specifications

- | | | | |
|-----------|-------------|-------------|---------------|
| • Heights | 4' 5' & 6' | • Diameters | 3.15" to 4.7" |
| • Nest | 5 tubes | • Bundles | 60 tubes |
| • Color | Light Green | • Ties | 2 x 10" |



Tel: 615 847 7039

Aberaman, Aberdare, CF44 6DA
South Wales, UK

e.mail: info@tubexusa.com

www.tubexusa.com



TUBEX
Advancing growth



TUBEX STANDARD PLUS TREESHelters

Specifications Data Sheet

TUBEX Standard Plus treeshelter with twin-wall tubular construction, laserline, manufactured from environmentally harmless polypropylene, with abrasion-reducing flared rim, added strengthening rods and pre-fitted releasable ratchet ties.

Material composition

- UV stabilized polypropylene, harmless to the environment
- Two nylon ratchet tie attachments

Standard sizes

- Heights: 4', 5' & 6' (tolerance: + 0-1")
- Diameters: 3.15" to 4.7", nested in 5 diameters to facilitate transportation and storage

Colors

- Specially blended light green

Special Features

- Flared rim to minimise stem abrasion
- Pre-fitted releasable ratchet ties for ease of installation and maintenance TUBEX Laserline - laser generated perforations forming a line of controlled weakness along the shelter, designed to burst as the tree fills the shelter

Durability

- Built-in strengthening rods, which prevent ties tearing away from shelter in strong winds (unique to TUBEX)
- Durable twin-wall construction for the best possible strength-to-weight ratio UV stabilized to provide an estimated lifespan of 5-7 years (can vary beyond this range depending on site conditions)

Applications

- Suitable for a wide range of planting stock and most site conditions, providing improved growth and survival rates plus reliable browsing and herbicide protection
- A cost effective alternative to traditional rabbit & deer fencing


Distributors



Features



Flared rim to minimize stem abrasion



Twin wall construction for rigidity and best strength to weight ratio




Laserline, designed to split avoiding strangulation as plant grows



UV stabilized and made from recycled plastic to provide minimum 7 year protection



Pre fitted thumb releasable ties for quick, easy installation and maintenance



Laserline, designed to split avoiding strangulation as plant grows

Tel: 615 847 7039

Aberaman, Aberdare, CF44 6DA
South Wales, UK

e.mail: info@tubexusa.com

www.tubexusa.com



TUBEX
Advancing growth